




ACCOYA.


Accoya modified timber has become the benchmark in the timber industry for performance and sustainability. No other wood offers the same combination of durability, stability, and versatility. Sourced from responsibly managed forests, Accoya is one of the few truly sustainable building materials available.





/ FEATURES /


- 

DURABILITY
Accoya is naturally resistant to termites, fungi and rot making it ideal for outdoor applications. Accoya even comes with a 50-year warranty above and a 25-year warranty in ground or freshwater.
- 

STABILITY
Accoya remains structurally sound with virtually no movement before, during and decades after the job is complete.
- 

AESTHETIC
Accoya has a clean, smooth finish that enhances its aesthetic appeal. It takes stain and paint exceptionally well, providing a consistent and attractive look in a wide range of finishes. Also available in coloured to the core grey.
- 

INSTALLATION
Accoya is easy and reliable to install thanks to its exceptional dimensional stability. It machines, cuts and fixes like a premium softwood, with minimal risk of splitting, cupping or warping. Its consistent performance allows for tighter tolerances, cleaner detailing and faster installation, delivering a high-quality finish that stays true long after the last nail is in.
- 

MAINTENANCE
Accoya requires minimal maintenance due to its high durability and stability. It does not need regular treatments like other softwoods, and its low maintenance profile means reduced time and cost for upkeep.
- 

SUSTAINABILITY
Certified FSC® ensures that all the wood comes from responsibly managed forests. Accoya is Cradle to Cradle certified® at the Gold Level and has achieved Platinum level for Material Health. Choosing Accoya helps reduce carbon emissions thanks to its low carbon footprint. Additionally, it is non-toxic, making it safe and is an environmentally friendly option for people, pets and the planet.

/ TECHNICAL INFORMATION /

ORIGIN	New Zealand
DURABILITY	Class 1
DENSITY	515 kg
HARDNESS	4.1 kN
RADIAL SHRINKAGE	0.4% (green to 12% M.C*)
TANGENTIAL SHRINKAGE	0.8% (green to 12% M.C*)
FIRE-RETARDANT PROPERTIES	Approximately BAL 19#
ENVIRONMENTAL CREDENTIALS	FSC® and Cradle to Cradle Gold certified®

The swatch provided is a general guide to the colour and grain.

*M.C = Moisture Content.

#BAL is subject to proper treatment and construction methods to comply with building regulations. Always consult a professional to confirm suitability for your specific situation based on the local BAL assessment.



**AUSTRALIAN
WOOD
INDUSTRIES.**

FOR MORE
INFORMATION

www.australianwood.com.au

1300 333 294

sales@australianwood.com.au

EMAIL

