


## BLACKBUTT.





Blackbutt is a durable, versatile hardwood prized for its warm, honey-toned hues and straight grain. Native to the east coast, it's a popular choice thanks to its natural fire resistance, strength, and contemporary aesthetic.





## / FEATURES /


- 

**DURABILITY**  
A naturally durable Australian hardwood, Blackbutt delivers strong resistance to decay and wear, making it well suited for demanding outdoor conditions.
- 

**STABILITY**  
Blackbutt offers reliable dimensional stability across varying climates, helping your project stay straight and true over time.
- 

**AESTHETIC**  
Characterised by a light, even colour palette with straight to slightly interlocked grain, Blackbutt provides a refined, architectural finish that suits both contemporary and classic designs.
- 

**INSTALLATION**  
Blackbutt's consistent density and workability support efficient installation, with pre-drilling recommended for optimal fixing performance.
- 

**MAINTENANCE**  
Requires minimal maintenance to preserve its appearance and durability. Periodic application of a protective finish helps maintain its natural colour and shields it from environmental factors.
- 

**SUSTAINABILITY**  
Responsibly sourced from managed Australian forests, Blackbutt is suitable for long-life applications, supporting sustainable building outcomes.

## / TECHNICAL INFORMATION /

ORIGIN	Eastern Australia (primarily NSW and QLD)
DURABILITY	Class 1 above ground
DENSITY	900 kg
HARDNESS	9.1 kN
RADIAL SHRINKAGE	4% (green to 12% M.C*)
TANGENTIAL SHRINKAGE	7% (green to 12% M.C*)
FIRE-RETARDANT PROPERTIES	Approximately BAL 29#
ENVIRONMENTAL CREDENTIALS	FSC® and PEFC certified

The swatch provided is a general guide to the colour and grain.

\*M.C = Moisture Content.

#BAL is subject to proper treatment and construction methods to comply with building regulations. Always consult a professional to confirm suitability for your specific situation based on the local BAL assessment.



**AUSTRALIAN  
WOOD  
INDUSTRIES.**

FOR MORE  
INFORMATION

[www.australianwood.com.au](http://www.australianwood.com.au)  
1300 333 294  
[sales@australianwood.com.au](mailto:sales@australianwood.com.au)

EMAIL

